## VUSION 7.4 BWR




## TECHNICAL DETAILS


| Product code                   | R74U01, R74A01, R74D01  |
|--------------------------------|---|
| Dimensions (mm)                | $175.3 \times 123.4 \times 13.2$ (without LED and Easylock)         |
| Display technology             | Full graphic E-ink display  |
| Active display area (mm)       | 161.6 × 97  |
| Resolution (pixels)            | 800 × 480   |
| Pixel density                  | 126 DPI   |
| Pixel colors                   | Black/white/red   |
| Viewing angle                  | Nearly 180°   |
| Usable pages                   | 4   |
| Label updates/hour/AP (CE/FCC) | 900 per datachannel, 3 channels max                                 |
| Operating temperature          | 10 °C to 40 °C  |
| Battery                        | 4 × CR2450  |
| Battery lifetime               | 5 years (2 updates/day)*  |
| Encryption                     | 128-bit AES   |
| Compliance                     | CE, ROHS, FCC/IC  |
| Packaging unit                 | 40 labels/box   |
| Active NFC                     | Yes   |
| LED                            | 1 × white, 1 RGB  |
| ESL operating frequency        | CE 868.0 - 869.8, FCC 921.525 - 926.475,<br>China 781.100 - 782.900 |
| Wireless firmware update       | Yes   |
|                                | *For details see product specification                              |

## EXAMPLARY PICTURE





TECHNICAL DRAWINGS





 ${\small \circledcirc}$  8/2018  $\bullet$  all specified values are subject to change by SES-imagotag www.ses-imagotag.com