

# VUSION 6.0 BWR



## TECHNICAL DETAILS

<b>Product code</b>	R60U01, R60A01, R60D01
<b>Dimensions (mm)</b>	138.1 x 104.7 x 12.4 (without LED and Easy-lock)
<b>Display technology</b>	Full graphic E-ink display
<b>Active display area (mm)</b>	114.9 x 85.79
<b>Resolution (pixels)</b>	600 x 448
<b>Pixel density</b>	128 DPI
<b>Pixel colors</b>	Black/white/red
<b>Viewing angle</b>	Nearly 180°
<b>Usable pages</b>	4
<b>Label updates/hour/AP (CE/FCC)</b>	750 per datachannel, 3 channels max
<b>Operating temperature</b>	10 °C to 40 °C
<b>Battery</b>	3 x CR2450
<b>Battery lifetime</b>	5 years (2 updates/day)*
<b>Encryption</b>	128-bit AES
<b>Compliance</b>	CE, ROHS, FCC/IC
<b>Packaging unit</b>	40 labels/box
<b>Active NFC</b>	Yes
<b>LED</b>	1 x white, 1 RGB
<b>ESL operating frequency</b>	CE 868.0 – 869.8, FCC 921.525 – 926.475, China 781.100 – 782.900

\*For details see product specification

## EXAMPLARY PICTURE



## TECHNICAL DRAWINGS

